



General Equipment list - North America









GENERAL SPECIFICATIONS _____

 Overall Length (L.O.A) Hull length L.W.L. Hull Beam Standard draft (Cast iron) Standard ballast weight (Cast iron) Performance draft (Cast iron/Lead) Ballast weight performance (Cast iron/Lead) Air draft 	14,15 m 13,17 m 12,82 m 4,25 m 2,15 m 3 300 kg 2,60 m 3 000 kg	46'5" 43'2" 42'1" 13'11" 7'1" 7,275 lbs 8'6" 6,612 lbs
 Aluminum mast version Carbon mast version Light displacement Fuel tank capacity (standard) Fresh water capacity standard Option Engine power Sail drive (standard) 	19,70 m 21,32 m 10 660 kg 200 L 370 L 200 L	64'8" 69'11" 23,495 lbs 53 US Gal 98 US Gal 53 US Gal

ARCHITECTS / DESIGNERS ____

- Naval Architect: BISCONTINI YACHT DESIGN
 Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION

- Category A 12 people (with ballast option: 6 people)
 Category B 12 people
 Category C 14 people

STANDARD SAILS DIMENSIONS ___

ALUMINUM CLASSICAL MAST

Classic mainsail	53 m²	5/0 sq/ft
Genoa		
 Furler below deck 	53 m²	570 sq/ft
 Furler under deck 	50 m²	539 sq/ft
• Code 0	95 m²	1,022 sq/ft
 Asymmetrical spinnaker 	170 m²	1,830 sq/ft
• 1	16,80 m	55'1"
 J -Furler below deck 	5,98 m	19'7"
 J -Furler under deck 	5,60 m	18'4"
• P	16,10 m	52'10"
• E	5,50 m	18'1"

CLASSIC MAST CARBON (+ 1,60 m / 5'3")

Classic mainsail	61 m²	657 sq/ft
Genoa		•
- Furler below deck	60 m²	646 sq/ft
 Furler under deck 	56 m²	603 sq/ft
• Code 0	105 m²	1,130 sq/ft
 Asymmetrical spinnaker 	207 m²	2,228 sq/ft
• 1	18,50 m	60'8"
 J -Furler below deck 	5,98 m	19'7"
 J -Furler under deck 	5,60 m	18'4"
• P	17,75 m	58'3"
• E	5,50 m	18'1"



General Equipment list - North America

STANDARD EQUIPMENT

CONSTRUCTION

- · Design made following European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Balsa sandwich infused hull
- Vacuum infused structural inner liner (Fabric resin) bonded to the hull
- Fiberglass sandwich, PET foam, balsa wood infusion deck, with diamond pattern non-slip coating
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Polyester bowsprit, 1 m / 3'3"
- Twin rudders affixed with stainless steel stock
- White hull Aluminum grey hull decoration
- 6 Hull portlights

DECK EQUIPMENT

RIGGING

- Anodized aluminum classical mast tapered, deck stepped, 2 Aft swept spreaders, Sparcraft, classic boom
- (or Black lacquered aluminum classical mast tapered, deck stepped, 2 Aft swept spreaders, Sparcraft, Black lacquered boom with LED lighting warm white)
 C-strand Rigging,
- C-strand stainless steel split backstay with manual hydraulic piston to starboard (hydraulic unit optional),
- Harken Element blocks at foot of mast
- Facnor Facsilde FR25 mainsail track (without traveller)
- 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
- Carbon classical mast tapered, deck-stepped (+ 1,60 m / 5'3", Weight saving: 75 kg / 165 lbs) 2 Aft swept spreaders, Sparcraft, Black lacquered boom with LED lighting - warm white

 - ROD Standing rigging
 Textile backstay crow's foot with manual hydraulic piston to
 - Harken Black Magic blocks at mast foot
 - Harken System A mainsail track (without traveller)
 - Mainsail sheets track in the bottom of the cockpit Harken 1,80 m/ 5'11" + track

Note: The carbon mast requires a mastjack (both for installation on delivery and for tensioning the shrouds during regattas), equipment not supplied by the yard.

- · Black lacquered aluminum rigid kicking strap with Dyneema tackle and friction rings
- Genoa tracks on the roof with traveller and hauling line controlled from the cockpit
- · Manual Genoa furler on the deck (Facnor Flatdeck)
- German system (Two-way mainsheet at the helm station) All lines lead back to the helm stations (except boom topping lift)
- Dyneema Complete running rigging:
- Mainsheet halyard sheave block,
- Genoa halyard,
- Boom uphaul (polyester) with cleat on mast,
- Mainsheet,
- 2 Genoa sheets,
- 2 Automatic reefing system lines
- · 8 halyard clutches to port, 4 to starboard
- Harken pulleys
- 2 Spinnaker sheet chain plates/code 0
- Running rigging hidden
- Lazy-jacks
- 2 Flag halyards

WINCHES

- 2 H46.2 STA manual self-tailing manoeuvre winches (at helm stations)
- 2 H50.2 STA manual self-tailing genoa winches (at helm stations)
- 2 Aluminum Speed Grip winch handles

Boast supplied without sail - Available as option

MOORING - ANCHORING GEAR

- Polyester bowsprit (1,00m / 3'3") with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker)
- Self-draining chain locker, Clench bolt, Hatch cover
- Single roller stainless steel bow fitting
 12 V 1 000 W vertical electric windlass Remote control in mooring locker
- 6 Anodised aluminum mooring cleats (Length: 0,30 m / 12")
- · Stainless steel chafing plate

SAIL LOCKER

Access through piston-driven cover

LED lighting

SAFETY ON DECK

- 1 Stainless steel open pulpit
- 2 Stainless steel aft pulpits with integrated fairlead
- 1 Stainless steel aft central pulpit (Height: 960 mm / 3'2")
- 2 stainless steel handrails on coachroof

- 1 Lifebuoy support bracket on aft pulpit Wooden flagstaff (1m / 3'3") with integrated support on pushpit Dual stainless steel lifelines and stainless steel stanchions (Height: 620 mm / 2") - Side boarding gate on either side
 • Emergency ladder on pushpit

COCKPIT

- Self-bailing cockpit
- Iro-Deck slatted
- 2 Sail lockers below cockpit seating
- Access hatch to tender garage
 Diesel deck filler at the aft of the side deck
- Shore power socket in port side storage
- Water deck filler located on forward roof on side deck
 Gas locker in the bottom of the cockpit
- Iro-Deck slatted cockpit benches
- Iro-Deck slatted side helmsman's seat
- Foldaway helmsman foot chock
- Black composite helm (diameter 900 mm/2'11") fixed on white lacquered aluminum pedestal
- Steering gear at the helm station Stainless steel steering chain transmission system
- 1 Emergency tiller
- 1 Steering compass
- Mechanical engine throttle and control panel on starboard
- 1 Cockpit shower with mixer tap in the tender garage
- 1 PPMA folding companionway door in the bottom of the cockpit -Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Usable dimensions: 0,93 m x 0,59 m x 0,33 m / 3'1" x 1'11" x 1'1")

 • Courtesy lighting (6 LED lighting points, warm white lighting)

SWIM PLATFORM / AFT TRANSOM

- · Fully opening transom, convertible into swim platform (2,32 m x 0,67 m / 77" x 2"2")

 1 Folding access step to the cockpit to starboard

- Manual openingIro-Deck slatted swim deck
- 1 Stainless steel removable bathing ladder (dedicated storage in starboard cockpit locker)

TENDER GARAGE

Accessible from the platform and from the cockpit

Can be used to house a Highfield Roll-Up type tender (2 m / 6'7")

1 Touch-operated ceiling LEDs



General Equipment list - North America

INTERIOR

- · Alpi teak woodwork and white painted wood
- Alpikord teak flooring Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- · Beige padded ceilings

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 1.98 m / 6'6"

- Salon companionway with 5 suspended Alpikord teak non-slip steps, LED lighting below each step
- 1 Leather-covered stainless steel handrail (DK02 chocolat color)

SALON

Headroom: 1,95 m / 6'5"

Port salon

- Alpi teak salon table with fixed top (can seat up to 6 diners)
- Face to face benches with large storages under seat
- Face to face salon convertible into double berth as option

Starboard salon

- Comfortable sofa facing the salon:
- seats with HR26 and HR30 foam
- softness thanks to the finish with hollow fibres + padding
- Storage under seating 115 V Power outlet
- 1 Electrical panel to starboard incorporated into a high cabinet
- · 2 T44 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below and above the portholes
- 1 Adjustable reading light
- Pillar with beige cover

CHART TABLE

to starboard from the companionway

- · Long chart table with fiddles, storage under the lifting top
- High cabinet with storage (or, in option, navigation screen)
- 1 Adjustable reading light
- 1 dual USB port1 115 V Power outlet

GALLEY - PORTSIDE

Headroom: 1,92 m / 6'4"

- · L-shaped kitchen
- Corian Glacier White work top with moulded Apli teak beading
- 1 1 rectangular stainless steel sink 1 Faucet with hot/cold water under pressure
- 1 Gas stove 2 burners Stainless steel/grill fitted on swivel joints (19 L) - Stainless steel protection handrail - Stowage below the oven with drop-down door
- 1 Storage unit with 1 door and 1 internal drawer for cutlery
- 190L / 50 US Gal icebox, with top and front opening
- Fitted cupboards and closed cubbyholes
- 1 Garbage bin (20 L)
- 1 Opened compartment along the side of the hull
- 1 Opening portlight with curtains in the coachroof side window

OWNER'S CABIN

Headroom: 1,93 m / 6'4"

- Central double bed (2,04 m x 1,12 m 1,60 m / 6'9" x 3'8" 5'3")
- Padding along the hull and at headboard: Beige PVC
- Bed access sideboard
- Chair on each side of bed
- 1 Hanger closet, with incorporated LED lighting
- 2 Flexible and adjustable bedside lamps
- T60 flush deck hatch with blind/mosquito net
- 1 Flush opening deck hatch (330 mm x 140 mm)
- 2 Portholes with rigid sliding blinds 1 115V power socket to starboard
- 1 dual USB port outlet on each side of the bed LED indirect lighting + 2 overhead lights

1 PRIVATE HEAD

to port

Headroom: 1,92 m / 6'4"

- Shower with foldable perspex door
- Manual marine toilet
- 1 64 L / 17 US Gal Rigid holding tank
- Counter-top in Corian Glacier White
- 1 Integrated polyester basin Mixer tap
- Cabinet Mirror
- Toilet accessories
- 1 Deck hatch with opaque film
- LED indirect lighting + Spot lighting

PORT AND STARBOARD AFT CABINS

Headroom: 1,94 m / 6'4"

- Double bed (2,04 m x 1,38 m / 6'8" x 4'6")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED
- Top-opening storage in front of the wardrobe
- 1 Opened compartment along the side of the hull
- 2 Flexible and adjustable reading lights
- 1 dual USB port
- 115 V Power outlet
- Porthole with rigid sliding blind
- Opening window with below cockpit seat with pleated blind
- 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,93 m / 6'4' Access through salon

- Shower separated with a perspex door 1 Mixer tap White polyester shower base
- Counter-top in Corian Glacier White
- 1 Manual marine toilet
- 64 L / 17 US Gal Rigid holding tank
- Washbasin 1 Mixer tap
- Cabinet + Storage space under the basin
- 1 Mirror
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- LED indirect lighting + 1 overhead light



General Equipment list - North America

ENGINE

- Engine Yanmar Diesel:
 57 CV/HP, Sail Drive, Common Rail (standard)
 Engine control at the starboard helm station Control panel
- Engine compartment:
- Soundproofing foam
 Ventilation: 2 air intakes and 1 forced air outlets
 1 Alternator (12 V / 125 Amp)
 1 Rotomolded diesel tank 200 L / 53 US Gal (under port aft berth) -Electronic gauge - Low level alarm - 1 Tank filling access
 • Filters: Sea water - Diesel - Water separator
- Foldaway three-blade propeller
- 1 Engine access through companionway (opening with 2 gas pistons)
- · 2 Engine access through aft cabins

PLUMBING

- 1 Rotomolded freshwater tank 330 L / 87 US Gal, under berth in forward cabin - 1 Tank filling access

 Waterpressure system - Expansion tank - Inline filter

 40 L / 11 US Gal Electric water heater (engine use)

 1 Rigid black water holding tank for each WC

- Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump

GAS

- 1 Compartment for 2 gas bottles in the anchor locker (diameter: $0.39 \times 0.39 \text{ m}$ / $1'3'' \times 1'3''$ Height: 0.51 m / 1'8'')
- Regulator and solonoid
- Gas leak detector

SMART BOARD

- "SEANAPPS" smart technology:
 For monitoring the boat's status and receiving alerts as well as maintenance advice via the associated mobile application.
 The type of information collected (GPS position, batteries, engine
- info, navigation data, etc.) varies according to the boat's configuration.



CONNECT YOUR BOAT FREE YOUR MIND

ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + Single USB port -Navicolor 2.4" screen
- 12 V Circuit
- 2 AGM service batteries 100 Amp
- 1 AGM engine battery 50 Amp Battery cut-off switch in the aft starboard cabin (under bed)
- 1 Battery charger (40 Amp)
- Load balancer
- 5 115V Sockets:
 - 1 in the forward cabin
- 1 in the aft cabins
- 1 in the salon (starboard)
- 1 at chart table
- 1 in galley
- 6 USB sockets:
 - 2 in the forward cabin
- 1 in the aft cabins
- 1 on the electrical panel
- 1 at chart table
- 1 Shore power socket 115 V, in the port cockpit locker

- LED lighting:
 Overhead lights
 Reading lights
 - Indirect light
- · LED navigation lights:
 - 1 Masthead light
- Steaming light
- 1 Mooring light on masthead

MISCELLANEOUS ITEMS

- · Smoke detector
- · Cleaning kit: eco-friendly cleaning products kit



General Equipment list - North America

TRIM LEVEL & PACKS

TRIM LEVEL _____

	CONFORT	LUXE
Coastal Pack (GARMIN)		
Windlass control with chain counter in cockpit		
Hifi: Fusion RA210 + 2 Interior speakers & 2 Waterproof exterior speakers		
Induction charging station for smartphones at the chart table		
Cabins: Mosquito nets for opening portholes		
LED indirect lighting	•	•
Navicolor 3.5" screen, Battery charge display		
IBS sensor		
• 2 Additional ancillary AGM batteries 12 V 100 A		•
Offshore Pack (GARMIN)		
 1 Solid wood cockpit table on stainless steel pedestal, 2 extension leaves, 1 opened central storage + Protective cover (Charcoal Grey) Electrical engine control on the starboard console 		•

ELECTRONICS PACKS: GARMIN_____

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
 Port and starboard helm stations: Steering console 1 12" GPS Map 1223 multi-function touchscreen (GPS, Chart plotter, Card reader - Bluechart G3 cartography included) 		-
 Wind Sensor gWind Race - pole 1m / 3'3":Windvane, Anemometer Airmar DST810 Sensor (Log, Speedometer, Temperature) PC interface (GND10) 315i VHF radio fixed to the chart table, without AIS receiver function Windex Windvane Protective covers for helm & consoles (Charcoal Grey) 		
 Reactor 40 Pilot with GHC 50 control on port console (LS40 hydraulic arm) Wireless autopilot remote control GARMIN Quatix 7 connected watch 		:

FASTNET PACK (implies pack Coastal or Offshore pack)

- 3 GNX120 7" mast screens + mast bracket + cover
- 800 AIS
 GHS11 VHF Wired handset at starboard helm station



General Equipment list - North America

RIGGING PACKS

DOWNWIND PACK (Compatible with the 3 masts)

- 2 HARKEN Black Magic blocks for spinnaker sheet/code 0
- HARKEN Black Magic block for spinnaker tackline with return on dedicated cleat in cockpit
- 1 Dyneema halyard with sheave block for spinnaker or Code 0
- Barber hauler (Chain plate on bulwark)

SELF-TACKING RIGGING PACK (Compatible with all masts and all rigging packs)

- · Self-tacking jib hardware (sheet only) 3 Blocks
- 1 Self-tacking jib track with traveller

SELF-TACKING STAYSAIL RIGGING PACK (Compatible with the 3 masts - requires the self-tacking rigging pack)

- 1 Wichard double chainplate on forward deck for removable forestay
- 1 Dyneema halyard with sheave block for staysail

ALUMINUM SAILS MAST PACK - NORTH SAILS

- Full-batten mainsail, 2 reefs (53 m²/570 sq/ft) and Genoa (50 m²/539 sq/ft or 53 m²/570 sq/ft depending on furler) North Sails NPL tour, laminated, dark grey
- Facnor travellers: 1 header traveller, 5 intermediate travellers, 5 batten travellers
- · Charcoal Grey lazy bag

CARBON MAST SAILS PACK - NORTH SAILS

- Full-batten mainsail, 2 reefs (61 m²/657 sq/ft) and Genoa (56 m²/603 sq/ft) North Sails NPL tour, laminated, dark grey
- Harken travellers: 1 header traveller, 6 intermediate travellers, 5 batten travellers
- · Charcoal Grey lazy bag

MOORING PACK

- Delta 20 kg/44 lbs anchor (galvanized steel)
 Chain (diameter: 10 mm / ³/₈" Length: 32 m / 105')
 Line (diameter: 18 mm / ¹¹/₁₆" Length: 45 m / 147')

- 4 XL (diameter: 300 mm / 12" Length: 880 mm / 2'11")
 2 L (diameter: 250 mm / 10" Length: 700 mm / 2'4")
 4 Moorings lines (diameter: 18 mm / ¹¹/₁₆" Length: 15 m / 49'3")

BLACK EDITION PACK

- 6 Black anodized aluminum mooring cleats (Length: 0,40 m / 1'4")
- Black lacquered stainless steel pulpits, handrails, stanchions
- · Textile lifelines with side boarding gates



Firet 44

General Equipment list - North America

OPTIONS

NAVIGATION ELECTRONICS: GARMIN

- Chart table: 12" GPS Map 1223 multi-function touchscreen
- 800 AIS
- · Panoptix PS51-TH (Forward underwater vision)
- Fantom 18x radar
- GHS11VHF wired handset at port helm station

RIGGING - SAILS

- Manual genoa furler below deck
 Code 0 with North Sails Xi 06 TF1,FX-4500 Facnor furler, dark grey laminated: 95 m² / 1,022 sq/ft (for aluminum mast)
 Code 0 with North Sails Xi 06 TF1,FX-4500 Facnor furler, dark grey
- laminated: 105 m² / 1,130 sq/ft (for carbon mast)
- Black lacquered aluminum classical mast
- Classic mast carbon (+ 1,60 m / 5'3", Weight saving: 75 kg / 165 lbs) 2 Aft swept spreaders + Black lacquered aluminium Racing boom
- with LED lighting + Mainsail sheet track at bottom of cockpit
 Harken hydraulic unit (Compatible with the 3 masts): Hydraulic textile backstay on piston,1 speed
- · Mainsail sheet track at bottom of cockpit (for aluminium mast)

WINCHES

- 1 Port electric H50.2 STAEH rigging winch, instead of standard
 1 Electric manoeuvre winch to port H50.2 STAEH, instead of standard
- · Upgrade for manual genoa winches H60.2 STA, replacing standard manual H50.2STA
- 2 Electric Harken (H60.2 STAEH) genoa sheet winches, replacing standard manual H50.2STA

HULL - DECK - COCKPIT

- Pearl grey gel-coat (Hull & Bowsprit), hull decoration white pearl
 Metallic hull paint (Hull, Aft transom, Bowsprit)
- Iro-Deck slatted side decks
- LED lighting of spreaders, for anodized aluminium mast, black lacquered aluminum mast, carbon mast
- Electric opening swim platform, Control at steering station + Remote control
- Water ballast in the aft cabins (not compatible with full boat air conditioning and heating options)
- Solar panels on the coachroof (400 W)
- Ballast Performance (Cast iron/Lead) Retractable bow thruster + 2 Dedicated batteries (50 Amperes 12 V) Control on starboard console
- White composite steering wheels
- Outboard engine bracket
- Polyester folding gangway (2,60 m / 8'6")
 Electric inflator/deflator for tender and fenders (portable, batterypowered)
- Shore freshwater supply
- 1,20 m/3'11" carbon flagstaff (instead of standard)

COCKPIT COMFORT

- Outside cockpit upholstery with backrests. Filter foam 80 mm/3" thickness (Density: 60F + 20S).
 - Sunbrellà Loop Sand
 - Dolce 51

EXTERIOR GUARDS

- Sprayhood with LED lighting, Strataglass windows, Charcoal Grey Bimini Charcoal Grey (sprayhood option required) Sunshade for the cockpit, Light Charcoal Grey (compatible with all booms)

INTERIOR EQUIPMENT

AMBIANT

· Internal upholstery according to color chart: Fabric, Leather, Nubuck, Ultra Leather

DOMESTIC APPLIANCES

3 burners ENO Grand Large Gas cooker + Tempered glass cover on the hotplate

ON BOARD COMFORT EQUIPMENT

- Berth in salon (Electric salon table pedestal + cushion matching the salon upholstery for Lounge area use) 12 V / 115 V inverter - 2 000 VA
- 1 200Ah Lithium batteries to replace the AGM batteries Weight saving: Approximately 110 kg / 242 lbs The lithium batteries can be used in exactly the same way as the greater number of AGM batteries that they replace. This technology allows 100% of the battery capacity to be used compared with 75% for
- the AGM batteries. The engine battery is still AGM.
 Additional water tanks (200L / 53 US Gal), under aft starboard cabin berth
- Sea water electric pump, in galley
- TECMA electric fresh water/sea water WC in the owner's head
- Quiet Flush fresh water/seawater electric WC in the aft starboard
- Spring mattress in the owner's cabin (thickness: 180 mm / 7"
- Air conditioning 16 000 BTU in salon and forward cabin (+ Shore socket extension cord 15 m / 49'3") - 32 A
- 24 000 BTU air conditioning full boat (only for use via shore power supply) + Shore socket extension cord 15 m / 49'3"
- Tableware Kit 6 people